This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.


| REVISIONS | | | | | | |
|-----------|---|---------|---------|----------|--|--|
| REV | DESCRIPTION | DATE | INITIAL | APPROVED | | |
| | REDRAWN FROM TATTERED ORIGINAL PER G.E. | 11/4/09 | RJC | RW | | |
| Α | CH'D -1 TO B/O. | 6/23/11 | RJC | RW | | |
| 1 | -2 CORRECTED .05 x 45° PLACEMENT WAS AT Ø.900 IS AT Ø.550. CH'D RADIUS WAS R.050 IS R.50. | 12/2/13 | RJC | GE | | |

® RED BARN MACHINE

RB23005426

REV 1

TITLE





ASSEMBLY

| | | | | | | | | | DWG NO. | JUIDE | - SPUF | ₹ |
|-----|-----------|-----|-------|-----|-------------|--------------|--------------------------------------|-----|---|------------|---------------------------------|---------------|
| | | | | | | | | | ADAI | PTER (| GÉARSH | 1AFT |
| | | | | | | | | | UNLESS OTHERWISE DIMENSIONS ARE IN | | DRAWN BY: | CLOUGH |
| | | | | | | | | | TOLERANCES ON: | N INCHES | APPROVED | 07 |
| ASS | YASSY | B/O | PART# | OTY | DESCRIPTION | MATERIAL | B/O INFORMATION OR SPECIFICATIONS | Pg. | DECIMALS .XXX ± .005 | ONS ± 1/32 | HEAT TREAT FINISH SPEC | |
| Qı | 1 411 | | 4 | 1 | | | | ١. | | GLES ±.5° | FINISH SPEC | |
| | | B/O | -1 | 1 | O-RING | | 2-014-N219-7 (PARKER) | 1 | -A L .1 | DECIFIED | | JSED ON MODEL |
| | | | -2 | 1 | GUIDE | STRESS PROOF | Ø1-1/8 x 2-1/2 | 2 | UNLESS OTHERWISE S 1. BREAK ALL SHARP | EDGES | | ALLISON |
| | | | -3 | 1 | PLUG | STRESS PROOF | Ø7/8 x 4-1/4 | 3 | .015 x 45° PR .015 2. DIMENSIONAL LIMITS APPLY A | | | |
| | ASS\ # | | | | | | | | SCALE NTS | DATE 11- | -4-09 | SHEET 1 O |

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

| | | REVISIONS | | | |
|---|-----|---|---------|---------|----------|
| | REV | DESCRIPTION | DATE | INITIAL | APPROVED |
| Ī | 1 | -2 CORRECTED .05 x 45° PLACEMENT WAS AT Ø.900 IS AT Ø.550. CH'D RADIUS WAS R.050 IS R.50. | 12/2/13 | RJC | GE |






(-2) GUIDE

SECTION A-A

| RB | RED | ВА | RN | 1 M | ACH | INE | - - | |
|-------------------------|------------------------------|---------------|-----------|-------------------------|-------------|-----|------------|--------|
| TITLE | RBa | 230 | 05 | 42 | 6-2 | | | |
| DWG NO. | ADAF | JUIDE Pter | - ? G! | SPI EARS | UR Shaft | | RE 1 | .v |
| | S OTHERWISE NSIONS ARE IN | | D | DRAWN E | | | Weil | |
| DECIMALS .XXX ± .005 | FRACTI | ONS ± 1/3 | 2 | HEAT TREAT FINISH | BLACK | | | |
| .x <u>∓</u> .1 | ANG OTHERWISE S | ELES ±.5° |) | SPEC | USED ON I | | <u>-</u> . | |
| | AK ALL SHARP | | | | ALLIS | ON | | |
| 2. DIMENSIO | NAL LIMITS APPLY A | FTER PLATI | NG | | | | | |
| SCALE | NTS | DATE | 11-4 | 1-09 | SHEET | 2 (| of (| 3 |

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

| | REVISIONS | | | |
|-----|-------------|------|---------|----------|
| REV | DESCRIPTION | DATE | INITIAL | APPROVED |
| | | | | |




 $\left(-3\right)$

PLUG

NOTE:
AFTER ENGRAVE MAKE SURE SHAFT
IS SMOOTH, BUFF IF NECESSARY.

| ® RED | BARN | I MA | CHINE | <u>-</u> |
|--|--------------------------|---------------------------------|-----------|-----------|
| rine RB | 23005 | 426 | -3 | |
| OWG NO. ADA | GUIDE - Pter ge | SPUF EARSH | R IAFT | REV 1 |
| UNLESS OTHERWISE DIMENSIONS ARE I TOLERANCES ON: | | DRAWN BY: APPROVED | CLOUGH | ⊣ Weil |
| | IONS ± 1/32 GLES ±.5° | HEAT TREAT FINISH SPEC | BLACK DX | IDE |
| UNLESS OTHERWISE 1. BREAK ALL SHARI .015 x 45° PR .01 2. DIMENSIONAL LIMITS APPLY | P EDGES 5 R | | ALLISON | |
| SCALE NTC | I | 1-09 | SHEET 2 | of 3 |

| | | REVISIONS | | | |
|---|-----|--|---------|---------|----------|
| I | REV | DESCRIPTION | DATE | INITIAL | APPROVED |
| | 1 | CH'D TITLEBLOCK & REVISION BLOCK, ADDED MISSING HOLE DIM P/N -2, ADDED ASSY. VIEW. | 7/9/09 | RJC | |
| | 1A | CH'D P/N -5 KEY RING DIA. FROM 1-5/8. | 9/25/09 | RJC | |



® RED BARN MACHINE

| QIY | QIY | D/O | I AIX I # | 3 | DESCRIPTION | MATERIAL | OR SPECIFICATIONS | |
|-----|------|-----|-----------|---|-------------|------------------|---------------------------|--|
| | | B/O | -1 | 1 | DRILL BLANK | HIGH SPEED STEEL | Ø3/16 x 3-1/2 REID #DB-12 | DWG NO. REV |
| | | | | | | | | DWG NO |
| | | | | | | | | UNLESS OTHERWISE SPECIFIED DRAWN BY: PERRITT |
| | | | | | | | | DIMENSIONS ARE IN INCHES TOLERANCES ON: APPROVED |
| | | | | | | | | DECIMALS .XXX ± .005 YX + .01 PRACTIONS ± 1/32 TREAT FINISH |
| | | | | | | | | X ± .1 ANGLES ±.5° SPEC |
| | | | | | | | | UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES |
| il | | | | | | | | .015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING |
| | ASSY | | | | | | | SCALE NTS DATE 8-15-07 SHEET 1 of 1 |